

# IncuMax™ WB10C & WB20C Water Baths



The IncuMax™ WB10C and WB20C water baths incorporate a seamless stainless steel bath and a PID microprocessor controller for precise temperature control. They also feature a pump to circulate and mix the bath water to ensure excellent temperature uniformity. A stainless steel gable cover for operating up to 100°C with minimum water evaporation is included.

MODEL	WB10C	WB20C
TEMPERATURE		
Range	1°C above ambient to 100°C	
Accuracy	0.1°C	
Uniformity	0.1°C	
Controller	Microprocessor	
Circulation	Pump to mix water for maximum uniformity	
Heater	1200 watts	
Safety Devices	Over-heating protection	
Working Bath Dimensions	11.6"W x 9.3"D x 5.9"H (295W x 235D x 15H) cm	19.5"W x 11.6"D x 5.9"H (49.5W x 29.5D x 15H) cm
Outside Dimensions	13.4"W x 11.0"D x 7.3"H (340W x 280D x 315H) cm	24.4"W x 13.4"D x 7.3"H (62W x 34D x 18.5H) cm
Bath Volume	10 liters	20 liters
Power Requirements	120V, 50/60 Hz, 10A (220V on request)	
Weight	22 lb (10kg)	29 lb (13 kg)



**Amerex Instruments, Inc.**

3951C Industrial Way  
Concord, California 94520  
925.299.0743 / Fax: 925.299.0745  
[www.amerexinst.com](http://www.amerexinst.com)  
[marketing@amerexinst.com](mailto:marketing@amerexinst.com)